(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 4 November 2004 (04.11.2004)

PCT

(10) International Publication Number WO 2004/095701 A1

(51) International Patent Classification7:

H03H 21/00

(21) International Application Number:

PCT/F12004/050045

(22) International Filing Date: 22 April 2004 (22.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 20035050

22 April 2003 (22.04.2003)

(71) Applicants and

(72) Inventors: BILCU, Radu [RO/FI]; Annalankatu 17 C 12, FI-33710 Tampere (FI). KUOSMANEN, Pauli [FI/FI]; Koivulehdonkuja 16, FI-36200 Kangasala (FI). EGIAZARIAN, Karen [AM/FI]; Maijalankatu 9 H 29,

- FI-33720 Tampere (FI).
- (74) Agent: TAMPEREEN PATENTTITOIMISTO OY; Hermiankatu 12 B, FI-33720 Tampere (FI).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: FILTERING METHOD AND AN APPARATUS



(57) Abstract: The invention relates to a method for filtering. In the method an adaptive filtering is performed to an input signal (x(n)). The filtered signal is further interpolated. The input signal (x(n)) is also interpolated for adapting the adaptive filtering. In the method the properties of the interpolation of the filtered signal are adaptable. The invention also relates to an apparatus (1) comprising an adaptive filter (2) for filtering an input signal (x(n)), a first interpolator (3) for interpolating the filtered signal, and a second interpolator (7) for interpolating the input signal (x(n)). The interpolated input signal is used to adapt the adaptive filter (2). The apparatus (1) further comprises a first adapting block (4) for adapting the properties of the first interpolator (3).

WO 2004/095701 A1



 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.